



PX-3230

THERMAL RECEIPT PRINTER



SMART KEYFEATURES

- SPEED UPTO 230MM/SEC.
- AUTO-CUTTER UPTO 1.5 MILLION CUTS.
- 100% JAPANESE MECHANISM.
- FRIENDLY UTILITIES | VIRTUAL USB.
- SUPPORT WALL MOUNTING.



PX-3230

THERMAL RECEIPT PRINTER



POS XPERT

SPECIFICATIONS OF PX-3230 THERMAL RECEIPT PRINTER

Model	PX-3230		
Printing	Print Method	Direct Thermal	
	Print Speed	230mm/s	
	Resolution	576dots/line or 572dots/line	
	Printing Width	72mm	
	Paper separator (opt)	48mm/52mm/56mm/64mm/68mm/76mm/80mm	
	Interface	Lan+USB	
Kitchen function	Power, Paper, Erro	Support	
	LED light with beeper	Without	
	Hanging device	Equipped	
Memory	Input buffer	256kbyte	
	NV Flash	256kbytes	
Fonts	Font A	12x24	
	Font B	9x17	
Fonts	Chinese	GB18030,BIG5 24x24dots	
	Japanese/Korea	Support	
	User-defined	Support	
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ ITF/ CODABAR/ CODE93/ CODE128	
Detection	Sensors	Paper out, Cover open, Cutter jam, Paper jam	
Power Supply	Input	AC 100V-240V 50/60HZ	
	Output	DC 24V/2.5A	
Paper	Paper Type	Thermal Receipt Paper	
	Paper Width(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm	
	Paper Thickness	0.06~0.08mm	
	Roll Dia	Max. Ø 83 mm	
	Paper Load	Easy paper loading	
	Paper Cut	Manual tear & Auto-cutter	
Physical Characteristics	Working Condition	0°C~45°C, 10%~80%RH	
	Storage Condition	-10°C~60°C, 10%~90%RH	
	Dimensions	191(D)x146(W)x12.9(H)mm	
	Net weight	1.84kg	Gross weight
Reliability	Printing head	150KM	
	Cutter	1.5 million	
Accessories	Data cable, Power adaptor, Power cable, Paper roll, CD, Manual.		
Packing	Individual box	Dimension 26X21X17cm(LXWXH)	1 unit/carton
	Master carton	Dimension 64X28X37cm(LXWXH)	6 units/carton
OS	Emulation	ESC/POS	
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS	
	SDK	Android, IOS	

SEGMENTS



Imported & Marketed by: Integrated Computer Services