


The new RP 3200 STAR. The retail printer that rules its category.



Print speed of 200 mm/sec in both text and graphic mode - Prints up to 60 bills/minute



Auto-cutter - 1.5 Million cuts; tear your bills neatly



Supports Windows 8



Energy star qualified for power efficiency



Print head life of 160 km



4 In 1 connectivity - Interface options : USB Standard (Optional : Parallel, Serial, Ethernet & Wi Fi)

The RP 3200 STAR Advantage

Today, the retail sector is changing rapidly – in both technology and service. Efficiency and speed are the keys to satisfying and retaining customers. That's why the new RP 3200 Star, with a print speed of 200 mm/sec, is one of the fastest in its category. It is Energy Star Level 5 qualified, decreases power consumption by 29 % and supports Windows 8 along with existing platforms. The RP 3200 Star not only comes with a built-in auto-cutter (with an improved life of 2 million cuts) but also USB connectivity and one other optional card (serial, parallel, WIFI or Ethernet).

Upgrade your billing standards now with RP 3200 Star, the thermal bill printer.

Specifications - RP 3200 STAR

Printing Method	: Direct thermal
Printing Speed	: 200 mm/sec
Dot Density	: 180 dpi
Dot Pitch	: 0,141mm
Character Per Line	: Font A=42 columns; Font B=56 columns
Character Set	: Alphanumeric characters 95, extended graphics 128 x 7 page (1 space page), International characters 32
Barcode Fonts	: UPC-A, UPC-E, JAN8 (EAN), JAN 13 (EAN), CODE 39, CODE 49, CODE 128, ITF, CODABAR, PDF 417, QR-CODE
Paper Width	: 50 mm - 82,5 mm
Paper Thickness	: 0,05 - 0,09 mm
Paper Roll Diameter	: Max. - 80,0 mm
Roll Core Inner Diameter	: 12,5 mm ±0,5 mm
Printing Width	: 72 mm, 512 dots/inch
Interface	: USB 1.1 selectable type (Parallel, Serial, Ethernet, WIFI)
Flash Memory	: 4 MB (32 MB Optional)

Logo Printing	: 1,5 MB memory for logo storing
Emulation	: ESC / POS
Driver	: Windows Printer Driver (8.7, XP, 2000, 2003, VISTA), WEPOS, Linux, OPDS, Java POS
Cash Drawer	: 1 Port
Reliability (Print Head Life)	: 160 km
MSRP	: 60,000,000 Lines
Sensor	: Paper End, Paper Low, Cover Open
Physical Dimensions (W x D x H)	: 152 x 202 x 150,5 mm
Auto Cutter Type	: Guillotine
Life	: 1,500,000 cuts
Cutting Method	: Full / partial cut
Power Supply	
AC	: 100V - 240V, 50/60 Hz
DC	: 24 Vdc/ 1,75 A
Operating Temperature	: 0° - 40°C
Storage Temperature	: -20° - 60°C
Operating Humidity	: 35% - 80%
Storage Humidity	: 10% - 90%
Warranty	: 1 year
Weight	: 1,7 kg

Best suited for printing

Bills / Receipts / Tickets / Gate Passes / Coupons / Tokens

CUSTOMER SEGMENTS



Supermarkets



Grocery Shops



Restaurants & Bars



Fast Food Joints



Airport



Lottery



Ticketing



Toll Gates

ORDERING INFORMATION

3003401002 RP 3200 STAR

OPTIONAL ACCESSORIES

SERIAL CARD

PARALLEL CARD

ETHERNET CARD

WIFI CARD

